



## 24-0105 Adjustable Height Peg Stand Instructions

Thank you for choosing Woodcraft peg stands. **Please read the following instructions completely before using your new stands.**

**Warning:** While the bike is on the peg stands, do not sit on or run the motorcycle. Never transport the motorcycle with the stands in place.

**DO NOT attempt to use these stands with folding foot pegs. These stands work with solid, non-folding foot pegs only.**

**Before Use-** Your bike should be placed on a set of regular stands that get the wheels off the ground. The Peg Stands will be installed on the pegs while the bike is still on the traditional stands.

**Installation-** Slide the stands over the footpegs with the bike on a traditional stand. The height should be adjusted to the tallest position that allows for the stand to hang from the peg without touching the ground.

**Height Adjustment –** If your stand cannot be slid on the footpeg without the base touching the ground, or if there is more than 1/2" inch of room below the stand, you need to adjust the height of the stand.

- 1- Remove the quick release detent pin
- 2- Un-clamp the quick release clamp
- 3- Select the proper height adjustment hole
- 4- Re-install the detent pin and tighten the clamp

Repeat the process on the other side – choosing the same hole location. Both Left and Right stands must always be used together.

**Remove the rear stand –** When adjusted properly the peg stands should hold the rear tire in the air. **IMPORTANT** - Be sure that both bases are sitting perfectly flat on the ground.

**WARNING:** You must **always use the detent pin** when using these stands. DO NOT rely on the clamping force of the quick release clamp alone to secure the upright – this will cause the bike to fall over.

Woodcraft Technologies Inc.  
105 Baldwinville Rd  
Winchendon, MA 01475  
978-297-2977  
[www.woodcraft-cfm.com](http://www.woodcraft-cfm.com)

